

# 22" Hand Sanitiser Network Android Advertising Display



### Hand Sanitising Digital Signage

In areas where hygiene is key, and hand washing facilities are not available, these displays are ideal. They combine a hand sanitising station\* with a versatile Digital Signage solution.



#### **Contactless Usage**

These displays come with a network upgrade and 1 year free subscription as standard so can be updated from our online CMS portal. They feature no external buttons or controls and have an automated on/off power timer to minimise contact following installation.









Free Network Upgrade & Subscription



24/7 Commercial Grade



3 Year Manufacturer's Warranty



**Complete Steel Enclosure** 



Integrated Android Media Player



**Automatic Dispensing** 



Easy Refill



Sanitiser Level Indicator



Compact and Lightweight Design



Optional Floor Stand











#### 3 Year Warranty

We offer a full commercial 3 year manufacturer's warranty and free lifetime technical support, giving you complete piece of mind.





#### 24/7 Usage

This is a true commercial grade solution. Built using a commercial grade LCD panel and components it is designed to be in constant use.



#### **Robust Steel Enclosure**

This solution features a full metal enclosure making it perfect for any commercial or public environment, especially in locations where impact is a concern.





#### **Optional Stand Available**

The display can be wall mounted as standard or mounted onto a stylish floor stand, for easy portability. The modern stand also features an illuminated blue LED strip.



# **Online Content Management System**

Using our user-friendly cost-effective software solution you can combine multiple media zones (images, videos, webpages etc.), social media feeds, scrolling text and RSS feeds for latest news.



## Plug and Play

If your internet connection goes down these displays can also be updated by copying your images and videos onto a USB stick and inserting into the display. Your images and videos will then play in a continuous loop.



#### **Fully Automated Dispensing**

The fully automated design removes the need to touch the dispenser, simply place your hand under the dispenser and a measured dose sanitiser will be dispensed. The dispense valve is non-spray, non-clog and non-drip.



# **Custom Modifications**

We can upgrade your display to have 4G connectivity, manufacture a touch screen version or even supply the display in different colours.



















PLUG AND PLAY UPDATE OPTION



24/7 COMMERCIALS GRADE



ROBUST STEEL ENCLOSURE



EASY SANITISER REFILL



REMOVABLE TRAY



SANITISER LEVEL INDICATOR



NETWORK UPGRADE



















Resolution   1080x1920   108			22 Inch
Panel         Aspect Ratio         16.9°           Vewing Angle         178°           Colour         16.7M           Contrast Ratio         5000-1           Brightness         45000/m2           Response time         5ms           Lifespan (hours)         70,000           Audio         HDMI, VGA           Auting         Audio Audio Socket (3.5mm)           Power         Power Consumption (W)         17           Power (nput         ACTIO-240V (50Hz-60Hz)           Mechanical         YES, Holes (mm)         350x800x101.2           Package Size (W.W.HxD mm)         350x800x101.2           Package Size (W.W.HxD mm)         TBD           Mechanical         YES, Holes (mm)         200x200           Mechanical         YES, Holes (mm)         200x200           Mechanical         YES, Holes (mm)         7           Mechanical         YES, Holes (mm)         200x200           Methylit (kg)         7         7           Gross Weight (kg)         7         7		Resolution	1080x1920
Panel		Display Area (mm)	266.95x475.38
Colour			16:9
Colour   16.7M   16		Viewing Angle	178°
Brightness			16.7M
Brightness			
Response time			
Lifespan (hours)   70,000			
udio         Built-in stereo speakers         3W x2           V Inputs         Video         HDMI, VGA           Audio         Audio Socket (3.5mm)           Ower         Power Consumption (W)         17           Power Input         AC110-240V (50Hz-60Hz)           Age (April 1)         AC110-240V (50Hz-60Hz)           Percentage Size (WAHAD mm)         350x800x101.2           Percentage Size (WAHAD mm)         TBD           Meter Weight (kg)         7           Operating Temperature         0 °C to 50 °C           Operating Temperature         0 °C to 50 °C           Operating Temperature         30°C to 60°C           Operating Humidity         10% to 80%           Storage Humidity         5% to 95%           Storage Humidity         10% to 80%           Storage Temperature         40 °C to 50°C           Operating Humidity         10% to 80%           Storage Temperature         40 °C to 50°C           Operating Temperature         40 °C to 60°C           Operating Temperature         40 °C to 50°C           Operating Temperature         40 °C to 60°C           Operating Temperature         40 °C to 50°C           Operating Temperature         40 °C to 50°C			
Vinputs         Video         HDMI, VGA           Audio         Audio Socket (3.5mm)           ower         Power Consumption (W)         17           power Input         AC110-240V (50Hz-60Hz)           package Size (WHAD mm)         350x800x401.2           Package Size (WHAD mm)         350x800x401.2           Package Size (WHAD mm)         1BD           VESA Holes (mm)         200x200           Net Weight (kg)         7           Gross Weight (kg)         7           Operating Femperature         0°C to 50°C           Storage Temperature         -30°C to 60°C           Operating Humidity         10% to 80%           Storage Humidity         10% to 80%           Media Fesolution         1920x1000/1080x1980x190           Internal Memory         6GB           CPU         Quad-Core Cortex-A17@1.61GHz           GPU         Mali-T760 MP4 @600MHz           RAM         2GB DDR3           ROM         8GB NAND           USB         USB.2 USB.2 HOST (x2)           LAN         10/100M Ethernet (Network Version O		and and help also	
Vinputs         Audio         Audio Socket (3.5mm)           ower         Power Consumption (W)         1.7           ower May Inguit         ACT10-240V (50Hz-60Hz)           tee Annical         Unit Size (WxHxD mm)         350x800x101.2           tee Annical         YESA Holes (mm)         200x200           Net Weight (kg)         7           Gross Weight (kg)         TBD           Operating Temperature         0 °C to 50 °C           Storage Temperature         -30°C to 60°C           Operating Humidity         5% to 95%           Media Formats         Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)           Media Resolution         1920x1080x1200           Internal Memory         6GB           GPU         Quad-Core Cortex-A17@1.61GHz           GPU         Mail-T760 MP4 @600MHz           GPU         Mail-T760 MP4 @600MHz           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           Vi-Fi         802.11b/gr/nac (Network Version Only)           Vi-Fi         802.11b/gr/nac (Network Version Only)           Vi-Fi         90.10cm           Gapacity (ml)         700 (each dose 0.8-1)           (ispenser <td< td=""><td>dato</td><td>·</td><td></td></td<>	dato	·	
ower         Power Consumption (W)         17           Power Input         AC110-240V (50Hz-60Hz)           Perchance         Unit Size (WxHxD mm)         350x800x10.12           Perchance         Package Size (WxHxD mm)         TBD           Perchance         VESA Holes (mm)         200x200           Net Weight (kg)         7           Gross Weight (kg)         TBD           Operating Temperature         0°C to 50°C           Operating Humidity         10% to 80%           Storage Humidity         10% to 80%           Media Formats         Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)           Media Resolution         1920x1080/1080x1920           Internal Memory         6GB           CPU         Quad-Core Cortex-A17@1.61GHz           GPU         Mali-T750 MP4 @600MHz           RAM         2GB DDR3           ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/1000M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           Graphic Engine         OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1           G			
ower         Power Input         AC110~240V (50Hz~60Hz)           I Uit Size (WxHxD mm)         350x800x101.2           Package Size (WxHxD mm)         TBD           VEXA Holes (mm)         200x2000           Net Weight (kg)         7           Gross Weight (kg)         7           Operating Temperature         0°C to 50°C           Storage Temperature         -30°C to 60°C           Operating Humidity         10% to 80%           Storage Humidity         5% to 95%           Media Formats         Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)           Media Resolution         1920x1080/1080x1920           Internal Memory         6GB           CPU         Quad-Core Cortex-A17@1.61GHz           GPU         Mali-Tr60 MP4@600MHz           RAM         2GB DDR3           ROM         8.GB NAND           USB         USB2.0 HOST (x2)           LAN         10/1000M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           Vispenser         Capacity (ml)         700 (each dose 0.8-1)           Sitropic Engine         OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3			
Unit Size (WxHxD mm)   350x800x101.2     Package Size (WxHxD mm)   TBD     VESA Holes (mm)   200x200     Net Weight (kg)   7     Gross Weight (kg)   TBD     Operating Temperature   0 °C to 50 °C     Operating Temperature   0 °C to 50 °C     Operating Humidity   10% to 80%     Storage Humidity   5% to 9%     Media Resolution   1920x1080/1080x1920     Internal Memory   6GB     OPU   Quad-Core Cortex-A17@1.61GHz     GPU   Quad-Core Cortex-A17@1.61GHz     GPU   Quad-Core Cortex-A17@1.61GHz     GPU   Quad-Core Cortex-A17@1.61GHz     GPU   Alail-T760 MP4 @600MHz     CPU   Quad-Core Cortex-A17@1.61GHz     GPU   Alail-T760 MP4 @600MHz     GPU   Alail-T760 MP4 @600MHz     CPU   Quad-Core Cortex-A17@1.61GHz     GPU   Alail-T760 MP4 @600MHz     GPU   Alail-T			
dechanical         Package Size (WXHXD mm)         TBD           dechanical         VESA Holes (mm)         200x200           Net Weight (kg)         TBD           Table           Tograting Temperature         0 °C to 50 °C           Storage Temperature         30°C to 60°C           Operating Humidity         10% to 80%           Storage Humidity         5% to 95%           Media Formats         Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)           Media Resolution         1920x10800/1080x1920           Internal Memory         6GB           CPU         Quad-Core Cortex-A17@.61GHz           GPU         Mali-T760 MP4 @600MHz           ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           WiFI         802.11b/g/n/ac (Network Version Only)           WiFI         802.11b/g/n/ac (Network Version Only)           Vispenser         OpenGL ES 1.1/2.0/3.0/3.1, OpenCt 1.1, Renderscript, Direct3D 11.1           Graphic Engine         OpenGL ES 1.1/2.0/3.0/3.1, OpenCt 1.1, Renderscript, Direct3D 11.1           Openser         Solution Type         Liquid/Foom/Gel (non-spray)           Openser         Flor Stand, Netw	Mechanical		
Idehanical Rehamical Re			
Net Weight (kg)         7           Gross Weight (kg)         TBD           Poperating Temperature         0 °C to 50 °C           Storage Temperature         0 °C to 50 °C           Poperating Humidity         10% to 80%           Storage Humidity         5% to 95%           Media Formats         Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)           Media Resolution         1920x1080/1080x1920           Internal Memory         6GB           GPU         Quad-Core Cortex-A17@1.61GHz           GPU         Mali-T760 MP4 @600MHz           RAM         2GB DDR3           ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           MV-Fi         802.11b/g/n/ac (Network Version Only)           Mispenser         Capacity (ml)         700 (each dose 0.8-1)           Siepenser         Sonsing Distance (cm)         5           Solution Type         Liquid/Foam/Gel (non-spray)           Cecessories         Included         Drip Tray, Scheduling Software, Remote Control, Key, User Manual           Coptional         Floor Stand, Network Version, Touch Screen Version, 4G Upgrade </td <td></td> <td></td>			
Gross Weight (kg)			
Operating Temperature         0 °C to 50 °C           Storage Temperature         -30°C to 60°C           Operating Humidity         10% to 80%           Storage Humidity         5% to 95%           Media Formats         Video (MPG, AVI, MP4, RM, RWB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)           Media Resolution         1920x1080/1080x1920           Internal Memory         6GB           CPU         Quad-Core Cortex-A17@1.61GHz           GPU         Mali-T760 MP4 @600MHz           ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           Major         Capacity (ml)           OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1           Cospecies         5           Solution Type         Liquid/Foam/Gel (non-spray)           Cocessories         Included         Drip Tray, Scheduling Software, Remote Control, Key, User Manual           Coptional         Floor Stand, Network Version, Touch Screen Version, 4G Upgrade			
Storage Temperature			
Operating Humidity	Environmental		
Storage Humidity			
Media Formats         Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)           Media Resolution         1920x1080/1080x1920           Internal Memory         6GB           CPU         Quad-Core Cortex-A17@1.61GHz           GPU         Mali-T760 MP4 @600MHz           RAM         2GB DDR3           ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           OS         Android 5.1.1           Graphic Engine         OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1           ispenser         5           Solution Type         Liquid/Foam/Gel (non-spray)           total Type         Liquid/Foam/Gel (non-spray)           total Type         Liquid/Foam/Gel (non-spray)           Total Type         Floor Stand, Network Version, Touch Screen Version, 4G Upgrade           tandards         Certification         CE, FCC & ROHS			
Media Resolution			
Internal Memory	Computer		
CPU         Quad-Core Cortex-A17@1.61GHz           GPU         Mali-T760 MP4 @600MHz           RAM         2GB DDR3           ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           OS         Android 5.1.1           Graphic Engine         OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1           Capacity (ml)         700 (each dose 0.8-1)           Sensing Distance (cm)         5           Solution Type         Liquid/Foam/Gel (non-spray)           Ccessories         Included         Drip Tray, Scheduling Software, Remote Control, Key, User Manual           Ccessories         Optional         Floor Stand, Network Version, Touch Screen Version, 4G Upgrade           Catandards         Certification         CE, FCC & ROHS			
AMM         2GB DDR3           ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           OS         Android 5.1.1           Graphic Engine         OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1           Osensing Distance (cm)         700 (each dose 0.8-1)           Sensing Distance (cm)         5           Solution Type         Liquid/Foam/Gel (non-spray)           Cecessories         Included         Drip Tray, Scheduling Software, Remote Control, Key, User Manual           Condards         Certification         CE, FCC & ROHS			
RAM         2GB DDR3           ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           OS         Android 5.1.1           Graphic Engine         OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1           Capacity (ml)         700 (each dose 0.8-1)           Sensing Distance (cm)         5           Solution Type         Liquid/Foam/Gel (non-spray)           Locessories         Included         Drip Tray, Scheduling Software, Remote Control, Key, User Manual           Cecessories         Optional         Floor Stand, Network Version, Touch Screen Version, 4G Upgrade           Landards         Certification         CE, FCC & ROHS			
ROM         8GB NAND           USB         USB2.0 HOST (x2)           LAN         10/100M Ethernet (Network Version Only)           Wi-Fi         802.11b/g/n/ac (Network Version Only)           OS         Android 5.1.1           Graphic Engine         OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1           Capacity (ml)         700 (each dose 0.8-1)           Sensing Distance (cm)         5           Solution Type         Liquid/Foam/Gel (non-spray)           Cecessories         Included         Drip Tray, Scheduling Software, Remote Control, Key, User Manual           Floor Stand, Network Version, Touch Screen Version, 4G Upgrade         CE, FCC & ROHS			
ROM			
LAN 10/100M Ethernet (Network Version Only)  Wi-Fi 802.11b/g/n/ac (Network Version Only)  OS Android 5.1.1  Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1  Capacity (ml) 700 (each dose 0.8-1)  Sensing Distance (cm) 5  Solution Type Liquid/Foam/Gel (non-spray)  Included Drip Tray, Scheduling Software, Remote Control, Key, User Manual Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade  tandards Certification CE, FCC & ROHS			
Wi-Fi 802.11b/g/n/ac (Network Version Only)  OS Android 5.1.1  Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1  Capacity (ml) 700 (each dose 0.8-1)  Sensing Distance (cm) 5  Solution Type Liquid/Foam/Gel (non-spray)  Included Drip Tray, Scheduling Software, Remote Control, Key, User Manual Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade Candards Certification CE, FCC & ROHS			
OS Android 5.1.1  Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1  Capacity (ml) 700 (each dose 0.8-1)  Sensing Distance (cm) 5  Solution Type Liquid/Foam/Gel (non-spray)  Included Drip Tray, Scheduling Software, Remote Control, Key, User Manual Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade tandards Certification CE, FCC & ROHS			
Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1  Capacity (ml) 700 (each dose 0.8-1)  Sensing Distance (cm) 5  Solution Type Liquid/Foam/Gel (non-spray)  Included Drip Tray, Scheduling Software, Remote Control, Key, User Manual Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade Central		Wi-Fi	802.11b/g/n/ac (Network Version Only)
Capacity (ml) 700 (each dose 0.8-1)  Sensing Distance (cm) 5  Solution Type Liquid/Foam/Gel (non-spray)  Included Drip Tray, Scheduling Software, Remote Control, Key, User Manual  Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade  tandards Certification CE, FCC & ROHS		OS	Android 5.1.1
Sensing Distance (cm) 5 Solution Type Liquid/Foam/Gel (non-spray)  Liquid/Foam/Gel (non-spray)  Liquid/Foam/Gel (non-spray)  Drip Tray, Scheduling Software, Remote Control, Key, User Manual Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade  Landards Certification CE, FCC & ROHS		Graphic Engine	OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1
Solution Type Liquid/Foam/Gel (non-spray)  Included Drip Tray, Scheduling Software, Remote Control, Key, User Manual Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade tandards Certification CE, FCC & ROHS	Dispenser	Capacity (ml)	700 (each dose 0.8-1)
Included   Drip Tray, Scheduling Software, Remote Control, Key, User Manual Optional   Floor Stand, Network Version, Touch Screen Version, 4G Upgrade Certification   CE, FCC & ROHS		Sensing Distance (cm)	5
Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade tandards Certification CE, FCC & ROHS		Solution Type	Liquid/Foam/Gel (non-spray)
Optional Floor Stand, Network Version, Touch Screen Version, 4G Upgrade tandards Certification CE, FCC & ROHS	Accessories	Included	Drip Tray, Scheduling Software, Remote Control, Key, User Manual
		Optional	Floor Stand, Network Version, Touch Screen Version, 4G Upgrade
Warranty Period 3 Year Warranty	tandards	Certification	CE, FCC & ROHS
Variable, Variable,	Warranty	Warranty Period	3 Year Warranty
Technical Support Lifetime		Technical Support	Lifetime

Errors and omissions excepted \*Hand sanitising liquid, foam or gel not included































